AGRICULTURAL EQUIPMENT MANUFACTURERS



Janke Australia Main Street, Mount Tyson Qld. 4356 Australia.

Ph: +617 4693 7188 Fax:+617 4693 7185

Email: info@janke.com.au Web: www.janke.com.au

JANKE Australia is a privately owned Australian Company specialising in the manufacture of machinery for the Grain and Cotton industries.

Universal Direct Drill Planters /Cultivators/Fixed Hitch/Floating Hitch/Linkage Planters

Parallelogram Force 500 and 400

Eliminators - Semi-Mounted/Trailing

Chisel Plough Planters

Rootcutters

Components and Spare Parts for existing machines - press wheels, tynes, cultivating points, inter-row cultivating points, plough sweeps, finger harrows, header extension fingers

Your Local Dealer:

GROW WITH JANKE. YOU'LL REAP THE REWARDS



Universal Hydraulic CHISEL PLOUGH/PLANTER

Primary Tillage Implement, Direct Drill Planter or Cultivator









Designed and Built in Australia for Australian Conditions

JANKE - Manufacturers of Agr

CHISEL PLOUGH / PLANTER



The Janke Universal Hydraulic Chisel Plough Planter can be used as a


Primary Tillage Implement Direct Drill Planter Cultivator

Grower input has led to the excellent trash clearance, high breakout tyne assemblies and an unmatchable robust frame construction.

Whether you have some major workingup to do, or direct drilling into huge amounts of stubble or cultivating, the Janke Chisel Plough will handle these conditions with hassle-free operation and dependability.

680kg (1500lb)Breakout ForceTyne Assembly.







Heavy Duty Depth Wheel Assembly



Tyne Trip Height



Hydraulic Tyne Box Assembly



ricultural Machinery Equipment

Specifications

AVAILABLE WIDTHS	9m	10.8m	12m	13.2m
TYNE SPACINGS	300mm	300mm	300mm	300mm
NUMBER OF TYNES	30	36	40	44
NUMBER OF TYNES ON CENTRE (c) & ON THE WING (w)	12c, 9w	12c,12w	16c, 12w	16c,14w
4-TYNE BEAMS	100 x 100 x 9mm RHS			
SPACING BETWEEN BEAMS	915mm between Beams 1 & 2, 3 & 4. 1320mm between Beams 2 & 3			
HYDRAULIC F-1500 TYNE ASSEMBLY	680kg (1500lb)			
Features of Hydraulic Tyne:				
- Reliable Janke design	\checkmark			
- 75 x 25mm Heat Treated Spring Steel Tyne Shanks	\checkmark			
- Tungsten on lower front face of Direct Drill Tyne Shank	\checkmark			
- Vertical shanks for better trash flow	\checkmark			
 - 680kg Breakout force (adjustable) 	\checkmark			
- Soft tyne recoil	\checkmark			
- Hardchrome pivot pins in Lubrite Pivot Bushes	\checkmark			
- 760mm (30") Underframe clearance	\checkmark			
- Vertical height adjustment with pin		``	1	
- 14" Chisel Plough sweeps	\checkmark			
LARGE TOOL BOX		`	1	
CARRY BASKET IN PULL		``		
WING STABILISER WHEEL ASSEMBLIES	14.5/60 X 18" 12 Ply Ground Hogs			
-Tandem heavy duty axles on main frame	\checkmark	<u> </u>	\checkmark	\checkmark
- Single heavy duty axles on wings	\checkmark	_	_	_
- Tandem heavy duty axles on wings		\checkmark	\checkmark	\checkmark
HYDRAULICS	Phasing Cylinders with Depth Stop & Levelling Adjustment			
	In-Line Micro Filters, clean phasing circuit			
OPTIONS AVAILABLE:	Wing fold cylinders with float capability			
- Janke Direct Drill shanks and points				
- Trailing press wheels, or				
In frame press wheels				
- 25mm, 38mm, 50mm or 100mm in width	<u>√</u>			
- Telescopic mount brackets for trailing press wheels			1	
- Folding floating 1,2,3 or 4 row harrows - fully adjustable		·		
- Air seeder pull for tow behind seeders			1	

