

AGRICULTURAL EQUIPMENT MANUFACTURERS



Janke Australia

Main Street,
Mount Tyson Qld. 4356
Australia.

Ph: +617 4693 7188
Fax: +617 4693 7185

Email: info@janke.com.au
Web: www.janke.com.au

JANKE Australia is a privately owned Australian Company specialising in the manufacture of machinery for the Grain and Cotton industries.

- Universal Direct Drill Planters /Cultivators/Fixed Hitch/Floating Hitch/Linkage Planters, F400, F500 and F650lb Breakout Tynes
- Parallelogram Force 500 and 400
- Eliminators - Semi-Mounted/Trailing
- Chisel Plough Planters
- Rootcutters

Components and Spare Parts for existing machines - press wheels, tynes, tyne shanks and adaptors, Janke planting points, finger harrows and header extension fingers.

Your Local Dealer:

GROW WITH JANKE. YOU'LL REAP THE REWARDS

AGRICULTURAL EQUIPMENT MANUFACTURERS

Janke



PARALLELOGRAM PLANTER

Superb Trash Handling and Precise Seed Placement



Designed and Built in Australia for Australian Conditions

Parallelogram Planter

Janke Australia is an Australian company specialising in the manufacture of No Till / Minimum Till Planting Equipment with Components and Spare Parts for your particular needs.



F500P with Inframe Presswheel

Rubberised Drum and Coulter



Level Lift Hitch



The Janke Parallelogram Planter gives:

- **Precise Seed Placement and Accurate Depth Control** using parallelogram planting units - this means each row sets its own depth regardless of frame height. *(generous 6" of travel-up and down from centre)*
- **Non Greaseable Long Life Bushes** with hard wearing pivot pins.
- **Superb Trash Handling** - Each row has a disc to cut the stubble with rubberised side drums to minimise hair pinning and control seed planting depth.
- **Spring Release or Hydraulic Tyne.**
- **Superior Flotation** for maximum manoeuvrability.
- **Quick and Simple Pin Adjustments** for independant seed depth and down pressure settings on each row.
- **Fertiliser Banding Attachments** can be provided as an option.
- **Presswheels** separately mounted either on parallelogram or on rear of frame available in a range of profiles.

Hydraulic Release Parallelogram



Inframe and Rear Mounted Presswheels



Parallelograms in working position



Agricultural Machinery Equipment

Specifications

Widths	: 3m/10' to 23.34m/75'
Tyne Spacings	: 250mm/10", 300mm/12", 333mm/13.3" or as per your requirements.
Frame Section Sizes:	: 3 Beams, : 100mm x 100mm x 6mm : RHS Standard : Sizes may vary depending on tyne spacing, wheels, broadacre or row crop requirements.
Inframe, or Trailing Press Wheels	
Spacing between beams	: 1520mm / 60" between beams
Spring Release Tyne Breakout Forces	: F200 Tyne 91kg/200lb : F400 Tyne 182kg/400lb : F500 Tyne 227kg/500lb
Hydraulic Tyne Breakout:	: 227-386kg Variable / 500-650lb

A wider range of specifications is available upon request.

Due to the constant product development, Janke reserves the right to alter the design and specifications shown on this brochure.



- **Janke Coulti Disc Parallelograms** give accurate seed placement. Choose either 16" or 18" Coulters to cut through huge amounts of stubble.
- **Large Hydraulic Fold and Lift Cylinders** with transport locks.
- **Clean Open Frame** design allows for superior trash flow.
- **Proven Janke Moisture Seeking Point.**

Our solution. We Listen. Grow with JANKE and you will reap the rewards.